

Fiche de Données de Sécurité

DELKOLOR – PEINTURE MULTISUPPORTS



RENSEIGNEMENTS CONCERNANT LE FOURNISSEUR DE LA FICHE DE DONNEES DE SECURITE

NOVODIS

4 RUE ANTOINE BECQUEREL
33600 PESSAC – FRANCE
Tel : 0 810 90 10 78
www.novodis.fr
commercial@novodis.fr

Numéro d'appel d'urgence

Pays	Organisation/Société	Adresse	Numéro d'urgence
France	Centre Antipoison Toxicovigilance de Paris Hôpital Fernand Widal	200 rue du Faubourg Saint-Denis 75475 Paris Cedex 10	+33 1 40 05 48 48

Danger

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains : acetone ; n-butyl acetate

(only for Germany)

WGK: 2

(only for France)

Classe A+

(only for car refinishing)

VOC 2004/42/EC Cat. II B e)

VOC max: 840 g/l

VOC cont: 600 g/l