


Product Datasheet

Alkaline

Alkaline Power



LR20APB


IEC Dimensions (mm)		
Dimension	Maximum	Minimum
A	61,5	
B		59,5
C		18,0
E	1,0	
F	9,5	
G		1,5
Ø	34,2	32,3

Name	LR20 / XL / D / AM1 / MONO / MN1300 / 13A / 13AC
Made in	Belgium
Type	Alkaline Foil
Nominal Voltage	1,5 Volt
Electrolyte	Potassium Hydroxide
Average weight	135,8 g
Storage temp. range	+10°C (50°F) ~ +25°C (77°F)
Operating temp. range	-20°C (-4°F) ~ +45°C (113°F)
Average Impedance	+/- 100 m-Ohm @ 1kHz fresh
Heavy metals	No added mercury (Hg), Cadmium (Cd) or Lead (Pb)
Compliant to	IEC 60086 non dangerous goods regulation EU directive 2006/66/EC
Recommended cut off voltage	0,8V per cell


Typical discharge values

LR20APB


Motor 1h/d 2,2 ohm end 0,8V




Stereo 2h/d 600 mA end 0,9V



Radio 4h/d 10 ohm end 0,9V



LIF 4m/h 24h/d 2,2 ohm end 0,9V



HIF 4m/15m 8h/d 1,5 ohm end 0,9V

